




Accessories

- 1 **VENTlick – WM 24365**
Adaptable humidifier without extra power supply and tubes
- 2 **VENTpower – WM 27630**
Optional external battery guarantees several hours of device operation
- 3 **VENTI-O₂ plus – WM 27200**
Adaptive oxygen valve without additional connection tube: no adverse effect on trigger and volume compensation from oxygen feed up to 15 l/min
- 4 **WEINMANNsupport – WM 93305**
PC software with converter cable USB-RS 485 (WM 93321) for setting and analysis

Our complete range of therapy solutions, accessories and mask systems is at: weinmann.de

Technical data for VENTImotion 2		CE 0197	
Product class as per 93/42/EEC:	II a	Ventilation modes:	CPAP, ST, T, TA
Dimensions (W x H x D):	230 x 120 x 280 mm	Respiratory frequency:	6 to 45 l/min
Weight:	approx. 3.7 kg	Accuracy:	±0,5 l/min
Temperature range		Increment:	1 l/min
■ Operation:	+5 °C to +35 °C	I:E ratio:	
■ Storage:	-40 °C to +70 °C	■ Inspiration time:	15% to 67% of respiratory period
Air pressure range:	600 – 1100 hPa (allows operation up to altitude of 4000 meters) automatic altitude adjustment	■ Increment:	1%
Electric connection:	115 – 230 V AC, 50 – 60 Hz tolerance -20% +10%	■ Accuracy:	±1%
Current consumption at:	230 V 115 V	Trigger level:	can be set at six levels, separate for inspiration and expiration, expiration trigger can be deactivated for ST mode
■ Operation:	0.17 A 0.3 A	Pressure increase/pressure decrease speed:	can be set at six levels
■ Standby:	0.050 A 0.108 A	Accuracy Volume measurement:	at 23 °C: ±15%
Classification as per EN 60601-1		Flow at max. motor speed at 0 hPa:	285 l/min ±15 l/min
■ Type of protection from electric shock:	protection class II	Flow at max. motor speed with bacteria filter at 0 hPa:	270 l/min ±15 l/min
■ Degree of protection from electric shock:	type BF	Heating of respiratory air as per HMV:	2.5 °C
Electromagnetic compatibility as per EN 60601-1-2		Pressure constancy measured as per DIN EN ISO 17510 in CPAP mode:	at 20 hPa: Δp ≤ 1 hPa at 14 hPa: Δp ≤ 1 hPa at 10 hPa: Δp ≤ 1 hPa at 7 hPa: Δp ≤ 0,5 hPa
■ Radio interference suppression:	EN 55011	Fine filter filtration degree up to 2 μm:	≥ 99.7%
■ Radio interference immunity:	EN 61000-3-2, EN 61000-3-3, EN 61000-4-2 to 6, EN 61000-4-8, EN 61000-4-11	Fine filter service life:	1000 hours with normal ambient air
Mean sound pressure level/ Operation as per EN ISO 17510 at a distance of 1 m from device in patient position:	at 20 hPa: about 32 dB (A) at 15 hPa: about 30 dB (A)# at 12 hPa: about 28 dB (A)# at 10 hPa: about 26 dB (A)# at 7 hPa: about 24 dB (A)	Allowed humidity for operation and for storage:	≤ 95% rel. humidity (no condensation)
Sound pressure level for alarm:	about 62 dB (A)	System resistance with air flow of 60 l/min at patient connection	
IPAP pressure range:	6 to 40 hPa	VENTImotion 2 with tube system WM 24130 and Silentflow WM 23600:	0,20 $\frac{kPa \cdot s}{l}$
EPAP pressure range:	4 to 20 hPa	VENTlick WM 24365 and bacteria filter WM 24148, VENTImotion 2 with O ₂ tube system WM 23737:	0,31 $\frac{kPa \cdot s}{l}$
CPAP pressure range:	4 to 20 hPa		
Pressure accuracy:	±0.6 hPa		
Increment:	0.2 hPa (1 hPa ≈ 1 cm H ₂ O)		
Minimum stable limit pressure (PLS _{min}) (min. pressure in event of fault):	≥ 0 hPa		
Maximum stable limit pressure (PLS _{max}) (max. pressure in event of fault):	≤ 60 hPa		



Now with new features!

- ✓ IPAP to 40 hPa
- ✓ Timed Adaptive (TA) mode
- ✓ VENTI platform operating concept



VENTImotion 2

Convincing Effectiveness

83494-EN-08/2013 © Copyright Weinmann, Hamburg. Duplication of any kind only with the express permission of Weinmann. All rights to design and specification modifications reserved.



VENTImotion 2 is now even more versatile.

- COPD
AirTrap
Control**
exhalation
monitoring
- COPD
Trigger
lockout time**
stable
exhalation
- COPD
Expiratory
ramp**
holds airways
open
- TA Mode**
optimum
synchronization
- Volume
compensation**
safety and
stability

More versatility with VENTImotion 2! That means more convenience and effectiveness for you with non-invasive, pressure-controlled ventilation.

Now with VENTImotion 2 you can increase inspiratory pressure up to 40 hPa – and thereby broaden your usage spectrum. The newly integrated TA mode (Timed Adaptive), which synchronizes the ventilator and the patient's breathing pattern, helps to reduce the patient's Work Of Breathing.

The proven combination of trigger lockout, exhalation monitoring AirTrap Control and expiratory ramp simplifies ventilation of COPD patients in particular. Thanks to the optimized regulation of tidal volume by means of volume compensation, VENTImotion 2 ensures a high degree of safety and stability.

Operating convenience

- Intuitive navigation with rotary dial and direct access to the most important ventilation parameters
- Softstart
- Numeric and graphic display of ventilation parameters
- Compatible with accessories for the VENTI product line

Safety

- Visual and acoustic alarms
- Optional back-up power supply provided by external rechargeable battery VENTIpower for up to seven hours of operation
- High flow of up to 300 liters/min for pressure constancy and leakage compensation.
- Weinmann Hygiene Concept complies with hygiene guidelines issued by Robert-Koch Institute.

More therapy comfort and convenience with our innovative features

■ TA mode (Timed Adaptive)

Controlled adaptive ventilation (TA mode) improves therapy compliance through optimized synchronization of ventilation with the patient's breathing pattern. The respiratory pump is effectively unloaded. The adaptive algorithm increases patient comfort and simplifies the setting process for the doctor.

■ Volume compensation

Optimum safety and stability of tidal volume. Three different speeds can be set for an increase in tidal volume. Volume compensation automatically switches to precise regulation upon reaching a corridor around the targeted volume in order to achieve the most precise setting for targeted volume.

Particularly suitable for COPD patients


■ Trigger lockout

Trigger lockout with high trigger sensitivity is effective protection from false triggering and trigger artefacts. This function ensures improved synchronization between patient and ventilator and thereby stabilizes the ventilation situation.

■ AirTrap Control

AirTrap Control helps to prevent dynamic hyperinflation and makes it possible for VENTImotion 2 to automatically regulate to the best frequency and expiration time for each patient.

With AirTrap Control – possible volume development in COPD



■ Expiratory ramp

The expiratory ramp is the temporary splint applied to the airways at the start of expiration to counteract an expiratory collapse. The expiratory flow remains higher on average, allowing the volume to be exhaled and the respiratory position to be lowered.



With humidifier VENTiClick and oxygen valve VENTI-O₂ plus



With VENTIpower



In the transport bag

Plus:

- ✓ IPAP to 40 hPa

Device description	WM Nr.
VENTImotion 2	27800
VENTImotion 2 with humidifier VENTiClick	27830